

United States of America  
Department of Transportation -- Federal Aviation Administration

Supplemental Type Certificate  
IMPORT

Number SA03094NY

This certificate issued to Beringer Aero  
Aeropole  
05130 Tallard  
France

Certifies that the change in the type design for the following product with the limitations and conditions therefore as specified hereon meets the airworthiness requirements of Part 3 of the Civil Aviation Regulations.

Original Product Type Certificate Number: 7A15

Make: Pilatus Aircraft Ltd.

Model: PC-6/B1-H2, PC-6/B2-H2, PC-6/B2-H4 series aircraft

Description of Type Design Change:

Installation of Beringer Aero's Wheel and Brake System is in accordance with their Maintenance and Overhaul Manual, MM-STC-002, Revision 2, dated April 5, 2012.

The following documents are required with this installation:

Instruction for Continued Airworthiness found in Beringer Aero document MC-STC-002, "Time Limits / Maintenance Checks", dated April 5, 2012.

Maintenance must be conducted in accordance with Beringer Aero document MM-STC-002, "and Overhaul Manual", dated April 5, 2012.

Limitations and Conditions:

1. The installer must determine whether this design change is compatible with previously approved modifications.
2. If the holder agrees to permit another person to use this certification to alter a product, the holder must give the other person written evidence of this permission.

This certificate and the supporting data which is the basis for approval shall remain in effect until surrendered, suspended, revoked or a termination date is otherwise established by the Administrator of the Federal Aviation Administration.

Date of application: January 14, 2011

Date reissued:

Date of issuance: May 14, 2012

Date amended:

By direction of the Administrator



*Franco Pier*

(Signature)

Gaetano Sciortino  
Acting Manager  
New York Aircraft Certification Office

(Title)

Any alteration of this certificate is punishable by a fine of not exceeding \$1,000, or imprisonment not exceeding 3 years, or both.